

BUSE 652 30° - 652 45°





Caractéristiques

- Très petit débit
- Angle réduit pour une pulvérisation localisée sur rang

Domaine d'application

- Pulvérisation localisée



30°-45°



1.5-5 bar



Méplat
10 mm



Types
F-G-I



INOX

Cod.	l/min		
	1.5 bar	2.0 bar	3.0 bar
652 30-0067	0.19	0.22	0.24
652 30-01	0.28	0.32	0.39
652 30-02	0.55	0.63	0.77

Cod.	l/min		
	1.5 bar	2.0 bar	3.0 bar
652 45-005	0.14	0.16	0.20
652 45-0067	0.19	0.22	0.27
652 45-01	0.28	0.32	0.39

652 30°	Vrac	652 45°	Vrac
	L'unité		L'unité
Matière Inox			
652 30-0067	727058	652 45-005	727057
652 30-01	727060	652 45-0067	727059
652 30-02	727095	652 45-01	727061

BUSE TP 65° - TP 80°



Caractéristiques



- Projection à jet plat
- Couverture uniforme
- Pulvérisation localisée

Domaine d'application

- Grandes cultures
- Faible débit



Cod.	l/min				
	2.0 bar	2.5 bar	3.0 bar	3.5 bar	4.0 bar
TP 65-005 (100M)	0.16	0.18	0.20	0.22	0.23
TP 65-0067 (100M)	0.21	0.24	0.26	0.28	0.30
TP 65-01 (100M)	0.32	0.36	0.39	0.42	0.45
TP 65-015 (100M)	0.48	0.54	0.59	0.64	0.68
TP 65-02 (50M)	0.65	0.72	0.79	0.85	0.91
TP 65-03 (50M)	0.96	1.08	1.18	1.27	1.36
TP 65-04 (50M)	1.29	1.44	1.58	1.71	1.82
TP 65-05 (50M)	1.61	1.80	1.97	2.13	2.27
TP 65-06 (50M)	1.94	2.16	2.37	2.56	2.74
TP 65-08 (50M)	2.58	2.88	3.16	3.41	3.65



65°-80°



2-4 bar



Méplat
8 mm



Type A



LAITON

TP 65°	Vrac
	L'unité
Matière Laiton	
TP 65-005	716974
TP 65-0067	716973
TP 65-01	716615
TP 65-015	716616
TP 65-02	716617
TP 65-03	716618
TP 65-04	716619
TP 65-05	716620
TP 65-06	716621
TP 65-08	716622

TP 80°	Vrac
	L'unité
Matière Laiton	
TP 80-005	716972
TP 80-0067	716971