

CABLE MONOCONDUCTEUR

Descriptif

- Tension nominale 600V
- Ame souple cuivre nu classe 5 IEC 60228
- Isolant PVC type TI2N FC 32-201-1- Gaine PVC type TM2 NF C 32-201-1 12V

(1) Couronne 100m	(2) Bobine 10m	Section	Compo. nominale	Ø ext. nominal (mm)	Masse linéique (kg/km)	Couleur
742909	712164	1mm ²	32x0.190	2.11	4	noir
742910	712161	1mm ²	32x0.190	2.11	4	rouge
742911	712162	1mm ²	32x0.190	2.11	4	vert
742912	712163	1mm ²	32x0.190	2.11	4	bleu
742913		1mm ²	32x0.190	2.11	4j	aune
742914		1mm ²	32x0.190	2.11	4	marron
742915		1mm ²	32x0.190	2.11	4b	lanc
742916	712228	1.5mm ²	28x0.245	2.52	0	noir
742917	712229	1.5mm ²	28x0.245	2.52	0	rouge
742918	712231	1.5mm ²	28x0.245	2.52	0	vert
742919	712230	1.5mm ²	28x0.245	2.52	0	bleu
742920	712232	1.5mm ²	28x0.245	2.52	0	jaune

(1) Couronne 100m	(2) Bobine 10m	Section	Compo. nominale	Ø ext. nominal (mm)	Masse linéique (kg/km)	Couleur
742921	712233	1.5mm ²	28x0.245	2.52	0	marron
742922		1.5mm ²	28x0.245	2.52	0b	lanc
742923	712234	2.5mm ²	47x0.245	3.03	1	noir
742924	712235	2.5mm ²	47x0.245	3.03	1	rouge
742925		2.5mm ²	47x0.245	3.03	1	vert
742926		2.5mm ²	47x0.245	3.03	1	bleu
742927		2.5mm ²	47x0.245	3.03	1j	aune
742928		2.5mm ²	47x0.245	3.03	1b	lanc
742929	712236	4mm ²	56x0.290	3.64	5	noir
742930	712237	4mm ²	56x0.290	3.64	5	rouge
742931		6mm ²	--		-	noir
742932		6mm ²	--		-	rouge



(1)



(2)