

Code			l/ha (spazio tra gli ugelli: 50 cm) l/ha (nozzle spacing: 50 cm)			
	bar	l/min	6 km/h	8 km/h	10 km/h	12 km/h
HCI4001	3	0.40	80	60	48	40
	4	0.46	92	69	55	46
	6	0.57	113	85	68	57
	8	0.65	131	98	78	65
	10	0.73	146	110	88	73
	12	0.80	160	120	96	80
	15	0.89	179	134	107	89
HCI40015	3	0.60	120	90	72	60
	4	0.69	139	104	83	69
	6	0.85	170	127	102	85
	8	0.98	196	147	118	98
	10	1.10	219	164	131	110
	12	1.20	240	180	144	120
HCI4002	3	0.80	160	120	96	80
	4	0.92	185	139	111	92
	6	1.13	226	170	136	113
	8	1.31	261	196	157	131
	10	1.46	292	219	175	146
	12	1.60	320	240	192	160
	15	1.79	358	268	215	179
HCI40025	3	1.00	200	150	120	100
	4	1.15	231	173	139	115
	6	1.41	283	212	170	141
	8	1.63	327	245	196	163
	10	1.83	365	274	219	183
	12	2.00	400	300	240	200
	15	2.24	447	335	268	224
HCI4003	3	1.20	240	180	144	120
	4	1.39	277	208	166	139
	6	1.70	339	255	204	170
	8	1.96	392	294	235	196
	10	2.19	438	329	263	219
	12	2.40	480	360	288	240
	15	2.68	537	402	322	268
HCI40035	3	1.40	280	210	168	140
	4	1.62	323	242	194	162
	6	1.98	396	297	238	198
	8	2.29	457	343	274	229
	10	2.56	511	383	307	256
	12	2.80	560	420	336	280
	15	3.13	626	470	376	313
HCI4004	3	1.60	320	240	192	160
	4	1.85	370	277	222	185
	6	2.26	453	339	272	226
	8	2.61	523	392	314	261
	10	2.92	584	438	351	292
	12	3.20	640	480	384	320
	15	3.13	626	470	376	313
HCI4005	3	2.00	400	300	240	200
	4	2.31	462	346	277	231
	6	2.83	566	424	339	283
	8	3.27	653	490	392	327
	10	3.65	730	548	438	365
	12	4.00	800	600	480	400
	15	4.47	894	671	537	447
HCI4006	3	2.40	480	360	288	240
	4	2.77	554	416	333	277
	6	3.39	679	509	407	339
	8	3.92	784	588	470	392
	10	4.38	876	657	526	438
	12	4.80	960	720	576	480
	15	5.37	1073	805	644	537