

TABLEAU DE DÉBIT

Cod.	BCPC/ASAE			l/ha (écartement latéral : 50 cm)						
		bar	l/min	6 km/h	8 km/h	10 km/h	12 km/h	14 km/h	16 km/h	18 km/h
WRC 110-015	F	2	0.49	98	74	59	49	42	37	33
	F	3	0.60	120	90	72	60	51	45	40
	F	4	0.69	138	104	83	69	59	52	46
	F	5	0.77	155	116	93	77	66	58	52
	TF	6	0.85	170	127	102	85	73	64	57
WRC 110-02	F	2	0.65	130	98	78	65	56	49	43
	F	3	0.80	160	120	96	80	69	60	53
	F	4	0.92	184	138	110	92	79	69	61
	F	5	1.03	207	155	124	103	89	77	69
	TF	6	1.13	226	170	136	113	97	85	75
WRC 110-025	F	2	0.82	164	123	98	82	70	62	55
	F	3	1.00	200	150	120	100	86	75	67
	F	4	1.15	230	173	138	115	99	86	77
	F	5	1.29	258	194	155	129	111	97	86
	F	6	1.41	283	212	170	141	121	106	94
WRC 110-03	F	2	0.98	196	147	118	98	84	74	65
	F	3	1.20	240	180	144	120	103	90	80
	F	4	1.39	278	209	167	139	119	104	93
	F	5	1.55	310	232	186	155	133	116	103
	F	6	1.70	339	255	204	170	145	127	113
WRC 110-04	F	2	1.31	262	197	157	131	112	98	87
	F	3	1.60	320	240	192	160	137	120	107
	F	4	1.85	370	278	222	185	159	139	123
	F	5	2.07	413	310	248	207	177	155	138
	F	6	2.26	453	339	272	226	194	170	151
WRC 110-05	F	2	1.63	326	245	196	163	140	122	109
	F	3	2.00	400	300	240	200	171	150	133
	F	4	2.31	462	347	277	231	198	173	154
	F	5	2.58	516	387	310	258	221	194	172
	F	6	2.83	566	424	339	283	242	212	189
WRC 110-06	M	2	1.96	392	294	235	196	168	147	131
	M	3	2.40	480	360	288	240	206	180	160
	M	4	2.77	554	416	333	277	238	208	185
	M	5	3.10	620	465	372	310	266	232	207
	M	6	3.39	679	509	407	339	291	255	226
WRC 110-08	M	2	2.61	522	392	313	261	224	196	174
	M	3	3.20	640	480	384	320	274	240	213
	M	4	3.70	740	555	444	370	317	277	247
	M	5	4.13	826	620	496	413	354	310	275
	M	6	4.53	905	679	543	453	388	339	302

TF	Très fines	< 119µm
F	Fines	119µm ÷ 216µm
M	Moyennes	217µm ÷ 353µm