

TABLEAU DE DÉBIT

Cod.	BCPC/ASAE			l/ha (écartement latéral : 50 cm)						
		bar	l/min	6 km/h	8 km/h	10 km/h	12 km/h	14 km/h	16 km/h	18 km/h
SF 080-01	F	2	0.33	66	50	40	33	28	25	22
	TF	3	0.40	80	60	48	40	34	30	27
	TF	4	0.46	92	69	55	46	39	35	31
	TF	5	0.52	103	77	62	52	44	39	34
SF 080-015	F	2	0.49	98	74	59	49	42	37	33
	F	3	0.60	120	90	72	60	51	45	40
	TF	4	0.69	138	104	83	69	59	52	46
	TF	5	0.77	155	116	93	77	66	58	52
SF 080-02	F	2	0.65	130	98	78	65	56	49	43
	F	3	0.80	160	120	96	80	69	60	53
	F	4	0.92	184	138	110	92	79	69	61
	F	5	1.03	207	155	124	103	89	77	69
SF 080-03	F	2	0.98	196	147	118	98	84	74	65
	F	3	1.20	240	180	144	120	103	90	80
	F	4	1.39	278	209	167	139	119	104	93
	F	5	1.55	310	232	186	155	133	116	103
SF 080-04	F	2	1.31	262	197	157	131	112	98	87
	F	3	1.60	320	240	192	160	137	120	107
	F	4	1.85	370	278	222	185	159	139	123
	F	5	2.07	413	310	248	207	177	155	138
SF 080-05	M	2	1.63	326	245	196	163	140	122	109
	F	3	2.00	400	300	240	200	171	150	133
	F	4	2.31	462	347	277	231	198	173	154
	F	5	2.58	516	387	310	258	221	194	172
SF 080-06	M	2	1.96	392	294	235	196	168	147	131
	M	3	2.40	480	360	288	240	206	180	160
	M	4	2.77	554	416	333	277	238	208	185
	M	5	3.10	620	465	372	310	266	232	207
SF 080-08	M	2	2.61	522	392	313	261	224	196	174
	M	3	3.20	640	480	384	320	274	240	213
	M	4	3.70	740	555	444	370	317	277	247
	M	5	4.13	826	620	496	413	354	310	275
SF 080-10	G	2	3.27	654	491	392	327	280	245	218
	M	3	4.00	800	600	480	400	343	300	267
	M	4	4.62	924	693	554	462	396	347	308
	M	5	5.16	1033	775	620	516	443	387	344

TF	Très fines	< 119µm
F	Fines	119µm ÷ 216µm
M	Moyennes	217µm ÷ 353µm
G	Grossières	354µm ÷ 464µm