

BUSES À JET PLAT STANDARD ET BASSE PRESSION



Caractéristiques

- Projection à jet plat
- Couverture uniforme
- Pulvérisation localisée

Domaine d'application

- Grandes cultures
- Faible débit




Cod.	l/min				
	2.0 bars	2.5 bars	3.0 bars	3.5 bars	4.0 bars
TP 65-005 (100M)	0.16	0.18	0.20	0.22	0.23
TP 65-0067 (100M)	0.21	0.24	0.26	0.28	0.30
TP 65-01 (100M)	0.32	0.36	0.39	0.42	0.45
TP 65-015 (100M)	0.48	0.54	0.59	0.64	0.68
TP 65-02 (50M)	0.65	0.72	0.79	0.85	0.91
TP 65-03 (50M)	0.96	1.08	1.18	1.27	1.36
TP 65-04 (50M)	1.29	1.44	1.58	1.71	1.82
TP 65-05 (50M)	1.61	1.80	1.97	2.13	2.27
TP 65-06 (50M)	1.94	2.16	2.37	2.56	2.74
TP 65-08 (50M)	2.58	2.88	3.16	3.41	3.65

BUSE TP 65° - TP 80°

TP 65°	Vrac
	L'unité
Matière Laiton	
TP 65-005	716974
TP 65-0067	716973
TP 65-01	716615
TP 65-015	716616
TP 65-02	716617
TP 65-03	716618
TP 65-04	716619
TP 65-05	716620
TP 65-06	716621
TP 65-08	716622

TP 80°	Vrac
	L'unité
Matière Laiton	
TP 80-005	716972
TP 80-0067	716971



65°-80°



2-4 bars



Méplat
8 mm



Type A



LAITON